

# GuestFridge 29 - Solid Black Door

GuestFridge 29 has been quality engineered with generous internal cabinet space, simple and stylish design, extremely low energy consumption and is a great value for all hotels. This popular 29 liter model serves 1.03 ft<sup>3</sup> of refrigeration space and features a handy can storage and even has room for tall bottles. In addition, this compact fridge is Energy-Star® compliant.

## Standard Features

- Energy Star® Compliant
- Quiet compressor technology
- Environmentally friendly R600a refrigerant
- Automatic Defrost
- ADA Compliant
- 1 shelf for maximum storage versatility and easy cleaning
- Shelf Dimensions: 3.35" (85mm)
- Tall bottle storage - great for large soda bottles
- Thermally insulated manufactured using 100% eco-friendly cyclopentane
- Adjustable thermostat
- Strong universal door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut closed
- Integrated door handle



**Solid Black Door**



## Technical Specifications

	GuestFridge 29 SBD
Energy Star® Compliant	Yes
Cooling Technology	Compressor
Capacity (liters / cubic feet)	29L / 1.03 Ft <sup>3</sup>
Dimensions HxWxD (inches) (mm)	19.3 x 15.1 x 16.14 490 x 384 x 410
Door Options	Solid Black Door
Door Hinge	Universal
Internal Shelves / Door Racks	1 / 2
Watts (W)	50W
Voltage (V) / Frequency (Hz)	110V / 60Hz 220V / 50Hz
Energy Consumption*	0.660 kWh/24 hr*
Net Weight (lbs / kgs)	31-34lbs / 14-15.5kgs
Temperature Range (°F / °C)	32-50°F / 0-10°C
Noise Level (dB)	≤39dB(A)
Defrost	Automatic
Interior Light	No
Certifications:	CCC/CB/CETL/CE/GS/RoHS/UL/CSA ISO 9001 2008/ISO 14001 2004

\*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.

\*\*Temperature Range with internal fan. Without internal fan temperature range is 6-14°C.




[www.MinibarSystems.com](http://www.MinibarSystems.com)

DOC0199\_GuestFridge-29-SBD-rev.1

MINIBAR SYSTEMS  
smart bars • smart people • smart solutions

## Ventilation

A minimum opening of 31 in<sup>2</sup> (200 cm<sup>2</sup>) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.



Minibar North America  
7340 Westmore Road  
Rockville, MD 20850  
tel 301 354 5055  
fax 301 309 1115  
info@minibarsystems.com