

# GuestFridge 48 - Solid Black Door

GuestFridge 48 has been quality engineered with generous internal cabinet space, simple and stylish design, extremely low energy consumption and is a great value for all hotels. This popular 48 liter model serves 1.69 Ft<sup>3</sup> of refrigeration space and features a handy can storage and even has room for tall bottles. In addition, this compact fridge is Energy-Star<sup>®</sup> compliant.

## Standard Features

- Energy Star<sup>®</sup> Compliant
- Quiet compressor technology
- Environmentally friendly R600a refrigerant
- Automatic Defrost
- ADA Compliant
- 3 shelf for maximum storage versatility and easy cleaning
- Shelf Dimensions: 4.5" & 8.6" (114mm and 218mm)
- Tall bottle storage - great for large soda bottles
- Thermally insulated manufactured using 100% eco-friendly cyclopentane
- Adjustable thermostat
- Strong universal door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handle



**Solid Black Door**



## Technical Specifications

	GuestFridge 48 SBD
Energy Star <sup>®</sup> Compliant	Yes
Cooling Technology	Compressor
Capacity (liters / cubic feet)	48L / 1.69 Ft <sup>3</sup>
Dimensions HxWxD (inches) (mm)	20 x 17.7 x 20 510 x 450 x 510
Door Options	Solid Black Door
Door Hinge	Universal
Wire Shelves / Door Racks	2 / 2
Watts (W)	60W
Voltage (V) / Frequency (Hz)	110V / 60Hz 220V / 50Hz
Energy Consumption*	0.605 kWh/24 hr*
Net Weight (lbs / kgs)**	36- 40lbs / 16.5-18kgs**
Temperature Range (°F / °C)	32-50°F / 0-10°C
Noise Level (dB)	≤41dB(A)
Defrost	Automatic
Interior Light	LED, Automatic
Certifications:	CCC/CB/CETL/CE/GS/RoHS/UL/CSA ISO 9001 2008/ISO 14001 2004

\*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.

\*\*Temperature Range with internal fan. Without internal fan temperature range is 6-14°C.




[www.MinibarSystems.com](http://www.MinibarSystems.com)

DOC0200\_GuestFridge-48-SBD-rev.1

**MINIBAR SYSTEMS**  
smart bars • smart people • smart solutions

## Ventilation

A minimum opening of 31 in<sup>2</sup> (200 cm<sup>2</sup>) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.



Minibar North America  
7340 Westmore Road  
Rockville, MD 20850  
tel 301 354 5055  
fax 301 309 1115  
info@minibarsystems.com