

GuestFridge 70 - Solid Black Door

GuestFridge 70 has been quality engineered with generous internal cabinet space, simple and stylish design, extremely low energy consumption and is a great value for all hotels. This popular 71 liter model serves 2.6 ft³ of refrigeration space and features a handy can storage and even has room for tall bottles. In addition, this compact fridge is Energy-Star® compliant.

Standard Features

- Energy Star® Compliant
- Quiet compressor technology
- Environmentally friendly R600a refrigerant
- Automatic Defrost
- ADA Compliant
- 3 shelf for maximum storage versatility and easy cleaning
- Shelf Dimensions: 4.5" & 8.6" (114mm and 218mm)
- Tall bottle storage - great for large soda bottles
- Thermally insulated manufactured using 100% eco-friendly cyclopentane
- Adjustable thermostat
- Strong universal door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handle



Solid Black Door



Technical Specifications

	GuestFridge 70 SBD
Energy Star® Compliant	Yes
Cooling Technology	Compressor
Capacity (liters / cubic feet)	71L / 2.6 Ft ³
Dimensions HxWxD (inches / mm)	26.96 x 17.72 x 20 / 685 x 450 x 510
Door Options	Solid Black Door
Door Hinge	Universal
Wire Shelves / Door Racks	3 / 3
Watts (W)	60W
Voltage (V) / Frequency (Hz)	110V / 60Hz / 220V / 50Hz
Energy Consumption*	0.605 kWh/24 hr*
Net Weight (lbs / kgs)	43.6- 48lbs / 19.7-21.7kgs
Temperature Range (°F / °C)	32-50°F / 0-10°C
Noise Level (dB)	≤41dB(A)
Defrost	Automatic
Interior Light	LED, Automatic
Certifications:	CCC/CB/CETL/CE/GS/RoHS/UL/CSA / ISO 9001 2008/ISO 14001 2004

*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.

**Temperature Range with internal fan. Without internal fan temperature range is 6-14°C.

www.MinibarSystems.com


DOC0201_GuestFridge-70-SBD-rev.1



MINIBAR SYSTEMS
smart bars • smart people • smart solutions

Ventilation

A minimum opening of 31 in² (200 cm²) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.



Minibar North America
7340 Westmore Road
Rockville, MD 20850
tel 301 354 5055
fax 301 309 1115
info@minibarsystems.com