GuestFridge 50 Slim - Solid Black Door

GuestFridge 50 Slim's have been quality engineered – with generous internal cabinet space, simple and stylish design, extremely low energy consumption and is a great value for all hotels.

Hotels are now able to offer guests the amenity they ask for and benefit from our fundamental commitment to develop sustainable products. Fridges come standard with interior LED light and internal racks.

Standard Features

- ADA Compliant
- Quiet compressor technology
- Removable glass shelving for easy cleaning
- Thermal insulation manufactured with eco-friendly cyclopentane
- Adjustable thermostat
- Strong universal door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handles
- Internal LED light
- Automatic defrost
- Anti-tilt brackets

Technical Specifications

	GuestFridge 50 Slim SBD	
Capacity (liters / cubic feet)	33L / 1.17Cu.Ft	
Dimensions HxWxD (inches) (mm)	20.5 x 17 x 16.14 520 x 432 x 410	
Door Options	Solid Black Door	
Door Hinge	Universal	
Chrome Shelves / Door Racks	2/3	
Watts (W)	85	
Voltage (V) / Frequency	110V / 60Hz 220V / 50Hz	
Energy Consumption*	0.62 kWh/24 hr*	
Net Weight (lbs / kgs)	31 / 14.06	
Certification:	CCC/CB/CETL/CE/GS/RoHS/UL/CSA ISO 9001 2008/ISO 14001 2004	

*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.



MINIBAR SYSTEMS

smart bars • smart people • smart solutions

www.MinibarSystems.com DOC0262_GuestFridge_50_Slim_CS_SBD




Solid Black Door





Ventilation

A minimum opening of 31 in² (200 cm²) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.



Minibar North America 7340 Westmore Road Rockville, MD 20850 tel 301 354 5055 fax 301 309 1115 info@minibarNA.com