GuestFridge 72 - Stainless Steel Glass Door

GuestFridge 72 has been quality engineered with generous internal cabinet space, simple and stylish design, extremely low energy consumption and is a great value for all hotels. This popular 72 liter glass door model serves 2.6 ft³ of refrigeration space and features a 2 pane tempered glass door. In addition, this compact fridge is Energy-Star® compliant.

Standard Features

- Energy Star® Compliant
- Quiet compressor technology
- Environmentally friendly R600a refrigerant
- **Automatic Defrost**
- ADA Compliant
- 3 shelf for maximum storage versatility and easy cleaning
- Shelf Dimensions: 4.5" & 8.6" (114mm and 218mm)
- Thermally insulated manufactured using 100% eco-friendly cyclopentane
- Adjustable thermostat
- Strong universal door hinges convertible left to right
- All-round magnetic seals to keep the door perfectly shut
- Integrated door handles



	GuestFridge 72 SSGD	
Energy Star® Compliant	Yes	
Cooling Technology	Compressor	
Capacity (liters / cubic feet)	72L / 2.6 Ft³	
Dimensions HxWxD (inches) (mm)	26.7 x 17.5 x 20 678 x 445 x 510	
Door Option	Stainless Steel Frame Glass Door	
Door Hinge	Universal	
Wire Shelves / Door Racks	3/0	
Watts (W)	60W	
Voltage (V) / Frequency (Hz)	110V / 60Hz 220V / 50Hz	
Energy Consumption*	0.605 kWh/24 hr*	
Net Weight (lbs / kgs)	43.6- 48lbs / 19.7-21.7kgs	
Temperature Range (°F / °C)	32-50°F / 0-10°C	
Noise Level (dB)	≤39dB(A)	
Defrost	Automatic	
Interior Light	LED, Manual	
Certifications:	CCC/CB/CETL/CE/GS/RoHS/UL/CS/ ISO 9001 2008/ISO 14001 2004	

^{*}Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371.











Ventilation

A minimum opening of 31 in² (200 cm²) for Intake, Shelf Cutout and Exhaust is required for proper ventilation.











^{**}Temperature Range with internal fan. Without internal fan temperature range is 6-14°C .